

Solid State High Power Amplifier Systems

2-6GHz /56dB Gain/56 dBm Psat/220AC

Model: TLPA2G6G-56-56-BC

TLPA2G6G-56-56-BC is a solid state high power amplifier systems provides high output power and high gain across the 2 to 6 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 2-6 GHz
- Gain: 56dB Min
- Psat Output Power:56dBm Min
- Protection:Over TEM,over voltage, over current ,output mismatch protection
- 50 Ohm Matched Input / Output


电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	2-6			GHz
增益 Gain	GP	56			dB
增益平坦度 Gain flatness	Δ GL		± 3		dB
饱和输出功率 Output Psat	Psat	56			dBm
线性输出功率 Output P1dB	P1dB		53		dBm
增益调节范围 Gain adjust range	Δ GR	30			dB
杂散 Spurious	Spur			-60	dBc
谐波 Harmonics	HAM		-15		dBc
输入驻波 Input VSWR	VSWRin		1.5	2.0	:1
交流电压 AC Voltage	Vac	220			V AC
电流AC Supply Current	Idc	16			A
阻抗 Impedance	I/O-IMP	50			Ohms

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	N Female/L29 Female	
监控和控制接口 Monitor and control interface	RS422 or Ethernet	
尺寸 Size	12U	
重量 Weight	150	Kg

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制 Control	RS422/Ethernet
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current protection 4,Output mismatch
控制功能 Control functions	1,Power setting On/Off 2,ALC
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD- 810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA2G6G-56-56-BC	Solid State High Power Amplifier Systems 2-6GHz,Gain:56dB,Psat:56dBm,220V AC,Built in Fan Cooling	Rev.1.0