

Solid State High Power Amplifier Systems

6-18 GHz /43dB Gain/43 dBm Psat/220 V AC

Model: TLPA6G18G-43-43-BC

TLPA6G18G-43-43-BC is a solid state high power amplifier systems provides high output power and high gain across the 6 to 18 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 6-18GHz
- Gain: 43dB Min
- Psat Output Power:43dBm Min
- Protection:Over TEM,over voltage, over current ,over VSWR protection.
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	6-18			GHz
增益 Gain	GP	43			dB
增益平坦度 Gain flatness	ΔGL		± 4		dB
ALC 精度 ALC Precision	ALC			± 0.5	dB
饱和输出功率 Output Psat	Psat	43			dBm
杂散 Spurious@Pout=43dBm	Spur			-60	dBc
谐波 Harmonics@Pout=43dBm	HAM		-15		dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac	220			V AC
功耗 Power Consumption	Pdiss	400@Max			W
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
程控接口 Network port Communication	DB-9	
尺寸 Size	19 Inch 2U	
重量 Weight	≤20	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制 Control	RS422/Ethernet,LCD Screen Display
显示功能 Display functions	1,Output Power 2,Reflect Power 3,Fault message
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current protection 4,Over VSWR
控制功能 Control functions	1,Power setting On/Off 2,ALC
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-45		+65	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:


标准型号 Base Number	描述 Desciption	版本号 Revision
TLPA6G18G-43-43-BC	Solid State High Power Amplifier Systems 6-18GHz,Gain:43dB,Psat:43dBm,220V AC,Built in Fan Cooling	Rev.1.0

典型曲线 Typical Performance Data:


Gain vs Frequency



Input VSWR vs Frequency




P1dB&P3dB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Pout@Pin



Pout@Equal_Pin




Harmonics vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

Spurious vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.