

Coaxial Bandpass Filter

12.5 GHz/SMA Female

Model: TLBF-12G5-1G6-E-Cryo

TLBF-12G5-1G6-E-Cryo is a coaxial bandpass filter with a passband Center frequency 12.5 GHz . The nominal insertion loss of the filter is 1.5 dB and the typical rejection is 40 dB.

Features:

- Passband Center Frequency:12.5 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts
- Field Replaceable RF Connectors

Applications:

- Instrumentations
- Radar Systems
- System Integrations


电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
通带中心频率 Passband Center Frequency		12.5		GHz
宽带 Band Width			1600	MHz
通带插损 Passband Insertion Loss			1.5	dB
带内波动 Pass Band Ripple			1.2	dB
带外抑制 Rejection	> 40dB@fc±2000MHz			dB
耐受功率 Power Handling			20	W
输入驻波 Input VSWR			1.5	:1
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
接口 Connectors	SMA Female	
尺寸 Size	40*14*10	mm

外形图 Outline Drawing: Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-12G5-1G6-E-Cryo	Coaxial Bandpass Filter, Passband Center Frequency :12.5GHz, Passband Insertion Loss:1.5dB, SMA Female	Rev.1.0